

ebaboard EP139 EF

milling-parameters



n = revolutions
z = number of teeth
d = diameter
vf = feed rate

$$n = \frac{vc \cdot 1000}{d \cdot \pi} \quad [1/\text{min}]$$

$$vf = n \cdot fz \cdot z \quad [\text{mm}/\text{min}]$$

$$fz = \frac{vf}{z \cdot n} \quad [\text{mm}]$$

$$vc = \frac{n \cdot \pi \cdot d}{1000} \quad [\text{m}/\text{min}]$$

The specified tools and cutting parameters are for reference only. They may vary depending on the machine tool and part size

Technical Datas	Machining 1	Machining 2	Machining 3	Machining 4	Machining 5	Machining 6	Machining 7
Strategy	Roughing Constant Z-	Profile Roughing	Roughing Pocket	Roughing Residual Material Z-Constant	Finishing Face Milling	Finishing Z-Constant	Engraving
Type of milling cutter	EMZ90 V22.042TH050 (1043249)	EBG V16.016AN140	DHC Ø12 INOX	EBG V12.012AN120-C (6128023)	EBG V10.010AN120-C (6130578)	EBG R08.008AP100-C (9148824)	Airline Kugel (1121894)
indexable inserts	VC GT 220530-ALM (1069759)	WPB 16 AF 30	-	WPB 12 CF 20 (6128107)	WPB 10 CF 10 (6129238)	WPR 08 DN (6131629)	-
cutting diameter [mm]	42	16	12	12	10	8	2
number of tool cutting edges	3	2	4	2	2	2	2
Radius [mm]	3	3	0	2	1	4	1
Cutting Speed vc [m/min]	600	500	340	500	450	380	100
Revolutions n [1/min]	4547	9947	9000	13262	14323	15120	15900
Feed per Tooth fz [mm]	0,5	0,4	0,15	0,3	0,15	0,2	0,1
Feed Rate vf [mm/min]	6820	7957	5304	7957	4297	6050	3180
Axial Depth of Cut ap [mm]	5	2,5	10	2	0,5	0,2	0,3
Radial Depth of Cut ae [mm]	30	3	6	8	6	0,5	0
Runtime [min]	6	10	1	1	3,5	90	1
Dust Formation	high	high	middle	middle	low	low	none



updated: 13.07.2026

ebalta Kunststoff GmbH | Erlbacher Straße 100 | 91541 Rothenburg o.d.T. - GERMANY | +49 9861 7007-0 | info@ebalta.com | www.ebalta.com